

# INSTALLATION INSTRUCTIONS

## Fuel Injector Wire Repair Kit.

SXS1000M3/M5  
-----  
SxS700M2/4  
Black connector 2018+  
Gray connector 2014-2017

Thank you for purchasing the Fuel Injector Wire Repair Kit for the Honda Pioneer and other ATV models.

### Kit includes:

- 2 Crimps (+1 extra)
- 2 small adhesive lined shrink tubes
- 1 large standard shrink tube
- 1 zip tie
- 1 HondaSxS Sticker

See detailed instructions at the following URL.

**Detailed instructions** → <https://hondasxs.com/threads/16786>

### Simple instructions:

- Remove seat back and heat shield to access both injectors.
- Trim wires to desired length.
- Strip back the ends of the wires ¼ of an inch on both OEM harness and repair kit.
- Insert shrink tubes. Small over the individual wires and Large over all of the wires.
- Twist the wire ends and use the Crimp to connect the wires together.
- Crimp 1 at a time. Double crimp each one and do a pull test to see if they pull out. We've included 1 extra crimp in case your pull test fails.
- Move the small shrink tube over the crimped connection.
- Heat to shrink (Heat gun is recommended). If using a lighter or blow torch be careful not to burn anything.
- Once both are done, pull the braided loom over the small shrink tube.
- Use the large shrink tube to further secure this section.

### HINT:

If the plug is hard to remove due to fine dirt buildup, try squirting it with some lubricant such as WD-40. Let it sit for moment, and then it should come free with ease.

If you need help or run into a problem please contact us. [Admin@HondaSxS.com](mailto:Admin@HondaSxS.com) Or HondaSxS.com  
Also, you can call us during normal business hours or text anytime – 704-802-9793  
Whatever the problem, even if your BUD is WISER and messed it up. We will get it taken care of!